



Product Number			Bore	Outer	Width	Width	Radius	Load Rating(N)	
Open	Shield	Sealed	Diameter d mm	Diameter D mm	B mm	B1 mm	rs min mm	Static Cor	Dynamic Cr
16026	16026 ZZ	16026 2RS	130	200	22	22	1	63400	52160
16024	16024 ZZ	16024 2RS	120	180	19	19	1	48400	40960
16022	16022 ZZ	16022 2RS	110	170	19	19	1	45700	36480
16021	16021 ZZ	16021 2RS	105	160	18	18	1	41600	32640
16020	16020 ZZ	16020 2RS	100	150	16	16	1	35300	28160
16019	16019 ZZ	16019 2RS	95	145	16	16	1	33800	26560
16018	16018 ZZ	16018 2RS	90	140	16	16	1	33200	24960
16017	16017 ZZ	16017 2RS	85	130	14	14	0.60	27000	21440
16016	16016 ZZ	16016 2RS	80	125	14	14	0.60	26500	25200
16015	16015 ZZ	16015 2RS	75	115	13	13	0.60	22800	21600
16014	16014 ZZ	16014 2RS	70	110	13	13	0.60	22400	20000
16013	16013 ZZ	16013 2RS	65	100	11	11	0.60	16900	13200
16012	16012 ZZ	16012 2RS	60	95	11	11	0.60	15900	12000
16011	16011 ZZ	16011 2RS	55	90	11	11	0.60	15600	11200
16010	16010 ZZ	16010 2RS	50	80	10	10	0.60	13000	9100
16009	16009 ZZ	16009 2RS	45	75	10	10	0.60	12400	8600
16007	16007 ZZ	16007 2RS	35	62	9	9	0.30	9900	6500
16008	16008 ZZ	16008 2RS	40	68	9	9	0.30	10600	7300
16006	16006 ZZ	16006 2RS	30	55	9	9	0.30	8900	5800
16005	16005 ZZ	16005 2RS	25	47	8	8	0.30	6000	3800
16004	16004 ZZ	16004 2RS	20	42	8	8	0.30	5500	3200

16000 Series

16000	16000 ZZ	16000 2RS	10	28	8	8	0.30	3600	1500
16001	16001 ZZ	16001 2RS	12	28	7	7	0.30	4000	1800
16002	16002 ZZ	16002 2RS	15	32	8	8	0.30	4400	2200
16003	16003 ZZ	16003 2RS	17	35	8	8	0.30	4800	2600